



400 CFM MAKOCAT (HV)

ELECTRIC CATALYTIC OXIDIZER / HIGH VACUUM SYSTEM

1270 N Red Gum St., Anaheim, CA 92806 - 714-630-4491 - www.makoindustries.us

The 400 Cfm Makocat (Hv) is a electric catalytic oxidizer / high vacuum system configured with the standard features and source-verified performance specifications presented below.

STANDARD FEATURES

- Compact footprint skid mounting
- Entrained Liquid Separator
- Dilution / Process Valves
- Stainless-steel Transfer Pump
- Oil Sealed Liquid Ring Blower
- Oil Cooler Assembly
- 25 HP TEFC Motor
- Sound Enclosure
- Platinum Coated Catalyst Cell
- Nickel Chrome Heating Element
- Stainless-steel Heat Exchanger
- Flame Arrestor
- Digital Temperature Controller
- Digital Dilution Controller
- Pitot Tube / Pressure Transmitter
- Digital Chart Recorder



AVAILABLE OPTIONS

Trailer Mounted System • Remote Telemetry • Totally Enclosed System • Single Phase System • UL Listed Electrical Enclosure E306379

STANDARD PERFORMANCE SPECIFICATIONS

SKID DIMENSIONS

7' Width x 7' Length x 13' Height

CONSTRUCTION

3/16" Heavy Duty Steel Construction Throughout

ELECTRICAL REQUIREMENT

208/240 Volt/3 Phase/200 Amp

ELECTRICAL REQUIREMENT

208/240 Volt/1 Phase/250 Amp

PROCESS FLOW


400 CFM and up to 28" Hg. Vacuum

VOC LOADING

3,500 PPMV Maximum

DESTRUCTION EFFICIENCY

98%+



MAKO INDUSTRIES

ELECTRIC CATALYTIC OXIDIZER

PROCESS INSTRUMENTATION DRAWING

DATE:
9/15/08

FILE:
400 Makocat.PID

400 CFM Makocat (HV)